

Power supplies

Model number
PS459034A

4.2 amp power supply

This compact general purpose 24 VDC power supply has an innovative DIN rail mounting system that holds even at vibration or lateral pressure. Spring clamp terminals are clearly arranged and user-oriented.


Features

- UL Class I, Division 2 approved
- Spring clamp terminals
- LED status indication




Specifications	
Output voltage	24-28 VDC (externally adjustable)
Output current	4.2 amps
Output ripple	50mVpp (max)
Input voltage	100 -120/200-240VAC (selectable)
Input current	2.1A / 1.0A (100VAC / 240VAC)
Efficiency	90.0% (100VAC)
Over voltage protection	36 VDC (max)
Over current protection	Yes
Over temperature protection	Yes
Holdup time	20ms
Area approvals	Class I, Division 2; T4A; groups A,B,C,D
Displays	Power ok, green LED
Operating temperature	-10°C to +70°C (+32°F to +140° F)
Storage temperature	-25°C to +85°C (-13°F to +185° F)
Housing	Non-metallic; DIN rail mounting
Dimensions (L, W, H)	103mm, 73mm, 75mm
Ingress protection	IP20, field enclosure required
Approvals	UL508, UL1950, cULus, CE,
Weight	360g (0.8 pounds)

Schematic drawing



output voltage
24 VDC

input line voltage





Valmet's professionals around the world work close to our customers and are committed to moving our customers' performance forward – every day.

Valmet Flow Control Oy

Vanha Porvoontie 229
01380 Vantaa, Finland
flowcontrol@valmet.com
+358 10 417 5000
valmet.com/flowcontrol

**Valmet Flow Control Inc.
Stonel product center**

26271 US Hwy 59, Fergus Falls, MN 56537 USA.
Tel. +1 218 739 5774.
sales.stonel@valmet.com
valmet.com/flowcontrol

