

Power supplies

Model number
PS459038A

8.0 amp power supply

This power supply is designed to provide power to the DeviceNet network and attached devices. This power supply meets all ODVA specifications for use with thick or thin cable.


Features

- NEC Class 1 and UL Class I, Division 2 approved
- Spring clamp terminals
- DC output ok (dry contact)




Specifications	
Output voltage	24.1 VDC ±0.2%
Output current	8.0 amps
Output ripple	50mVpp (max)
Input voltage	Universal 100 - 240VAC (50-60Hz)
Input current	2.3A - 1.0A (100VAC / 240VAC)
Power factor	0.99 / 0.92 (100VAC / 240VAC)
Efficiency	92.3% / 92.7% (100VAC / 240VAC)
Over voltage protection	29.5 VDC (max)
Over current protection	9.5 amp (max)
Turn-on time	85ms
Turn-on delay	600ms
Holdup time	32ms
NEC power class	NEC Class 1
Area approvals	Class I, Division 2; T4; groups A,B,C,D
Displays	Power OK, green LED Overload, red LED
Operating temperature	-25°C to +70°C (+14°F to +140°F)
Storage temperature	-40°C to +85°C (-40°F to +185°F)
Housing	Al/Mg alloy DIN rail mounting
Dimensions (L, W, H)	124mm, 60mm, 117mm
Ingress protection	IP20, field enclosure required
Approvals	UL508, UL1950, cULus, CE
Weight	900g (2.0 pounds)

Schematic drawing



output voltage
24 VDC

input line voltage





Valmet's professionals around the world work close to our customers and are committed to moving our customers' performance forward – every day.

Valmet Flow Control Oy

Vanha Porvoontie 229
01380 Vantaa, Finland
flowcontrol@valmet.com
+358 10 417 5000
valmet.com/flowcontrol

**Valmet Flow Control Inc.
Stonel product center**

26271 US Hwy 59, Fergus Falls, MN 56537 USA.
Tel. +1 218 739 5774.
sales.stonel@valmet.com
valmet.com/flowcontrol

